



Portland Mine Report No.111 – November 2023

Stonehills Mine is well underway and we heading towards 1,000m3 of clean Whitbed in Stock



Technical Manual:


Albion Stone has written the technical manual with the assistance from key experts in the stone industry. The manual seeks to provide information relating to the typical uses of Portland Stone which include cladding, internals, landscaping and ornate decorative stonework. Please look at the website: www.albionstone.com/technical-manual

Block Orders:

To discuss any individual block requirements or to place an order, please contact Tony Booker on 07768 077439 or email **tonybooker@albionstone.com**. Alternatively you can call the Portland office on 01305 860369.

Samples:

Typical samples of the various Portland stones are available for immediate despatch. Please request via enquiries@albionstone.com





Portland Stone

The scans on the right are indicative samples - please see the Range Panels at Portland for the full geological characteristics of the stones.

Grove Whitbed ®







| Maximum Block Sizes | Overall Size | 10.44m³ | 6.98m³ | 9.71m³ | 7.04m³ |
|---|---|-------------------|-----------------|-----------------|-----------------|
| | Length | 4.40m | 4.00m | 4.70m | 3.60m |
| | Bed Height | 2.90m | 2.30m | 2.70m | 2.60m |
| Average Block Sizes (Recent production) | Overall Size | 1.95m³ | 1.17m³ | 1.19m³ | 0.98m³ |
| | Length | 1.60m | 1.37m | 1.41m | 1.17m |
| | Bed Height | 1.02m | 0.84m | 0.87m | 1.04m |
| Current Availability: Shows the unallocated stock over the next 0-3 months. | | 11,000 - 13,000m³ | 3,000 - 4,000m³ | 4,500 - 5,000m³ | 500 - 750m³ |
| Future Ave Shows the estimated and planned product 12 mo | d unallocated stock ion over the next 3- | 13,000 - 15,000m³ | 4,000 - 5,000m³ | 5,000 - 5,500m³ | 1,000 - 1,500m³ |





Portland Stone


The scans on the right are indicative samples - please see the Range Panels at Portland for the full geological characteristics of the stones.

Bowers Whitbed and Basebed Blocks are still available upon request

Bowers Roach ®







| | Overall Size | 4.32m³ | 3.85m³ | 6.68m³ | 8.40m³ |
|---|--------------|-----------------|---------------|---------------|----------------|
| Maximum Block Sizes | Length | 4.00m | 2.80m | 2.50m | 3.40m |
| | Bed Height | 2.00m | 2.20m | 2.90m | 2.10m |
| Average Block Sizes (Recent production) | Overall Size | 0.95m³ | 0.68m³ | 3.14m³ | 3.58m³ |
| | Length | 1.61m | 1.02m | 1.58m | 1.75m |
| | Bed Height | 0.50m | 1.03m | 1.66m | 1.54m |
| Current Availability: Shows the unallocated stock over the next 0-3 months. | | 1,000 - 1,500m³ | 750—1,500m³ | 1,500—2000m³ | 750 - 1000m³ |
| Future Availability: Shows the estimated unallocated stock and planned production over the next 3- 12 months. | | 1,500 - 2,000m³ | 1,500—2,000m³ | 3,000—4,000m³ | 1000 - 1,250m³ |



Range Panels for Block Sales

The Albion Stone Range Panels are principally intended to act as a reference for the geological features in finished stones being produced within our factory. It is not easy to closely assess the finer characteristics of raw, freshly mined blocks before they have been cut with a precision stone saw in a manufacturing environment. We will make every reasonable attempt to ensure that the blocks supplied, exhibit features broadly similar to those shown in the Factory's range panels. However, we do strongly encourage customers to come to the mines and select their own blocks with the aim of ensuring that the stone being extracted at the time conforms to their individual customers' expectations.

We are happy for any block customer to use the range as an indication of the geological feature present in the stone, but we would strongly recommend that the customer clearly identifies an acceptable range from slabs at their factory that can be used as part of their quality control system and manages the client's expectations of this natural product.

It is important to remember that any geological feature demonstrated by our range panels will not be considered as a flaw unless their concentration becomes so great that the typical character of the stone is lost.

We would strongly recommend that any customers adopt the same principles with their clients and note that the wording has been copied from internationally accepted BSEN 1469 the standard for Natural Stone Products.

Block loading requirements:

For safety reasons, all lorries must have timbers (these can be purchased from us) and all loads must be strapped down. Lorries will not be loaded without them. Due to Brexit, all export deliveries now need to be on treated timbers which can also be purchased from us.





